



## Christie Access Series LCD panels

The perfect balance between performance and price

Technical specifications		Christie UHD551-L	Christie UHD651-L
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm
	native resolution	• UHD 3840 x 2160 (16:9)	
	backlight	• Edge-lit LED	
	LED lifespan	• 50,000 hours to 50% brightness	
	display orientation	• Landscape	
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm
	nominal bezel size (bottom/side/top)	• 14mm/11mm/11mm	• 21mm/15mm/15mm
	brightness	• 400 nits (cd/m <sup>2</sup> ) typical	
	contrast ratio (full field)	• 1200:1 typical	• 4000:1 typical
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 60Hz	
	response time	• 8 ms typical	
	color space (CIE 1931)	• 68% typical	• 75% typical
	display colors	• 10 bit, 1.07 billion colors	• 8 bit, 16.7 million colors
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • 2 x USB 2.0 • USB 3.0	
	outputs	• DisplayPort 1.2a; HDMI 2.0	
Audio	inputs	• RCA (L/R) line in	
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender	
Power	input rating	• 100-240 VAC @ 50-60Hz	
	power consumption	• 70W typical without OPS • 140 W maximum without OPS • <=0.5W in standby without OPS	• 73W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS
Environment	operating temperature	• 32-104°F (0-40°C)	
	storage temperature	• -4-140°F (-20-60°C)	
	operating humidity	• 20-90% RH non-condensing	
Physical	size (panel only)	• (WxHxD) 48.7 x 28 x 4.1" (1238 x 712 x 104mm)	• (WxHxD) 57.4 x 33.1 x 3.8" (1459 x 841 x 96mm)
	weight	• 38.6lbs (17.5kg)	• 49.6lbs (22.5kg)
	mounting	• VESA 400 x 200mm, M6	• VESA 400 x 400mm, M6
Runtime		• Designed for 16/7 operation featuring a reliable power supply <sup>1</sup>	
Features		• Commercial grade LCD with LED backlight • OPS slot • Anti-glare treatment • 2 x 8W speakers • On/off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Source switching for failover • Kensington lock • Wi-Fi® • Bluetooth • Miracast device connectivity • Pixel shifting	
Accessories		• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA551 up to 10 point IR touch overlay (for 55") and TA651 up to 10 point IR touch overlay (for 65")	
Warranty		• Three year parts and labor limited warranty • Contact an authorized Christie representative for full details	

<sup>1</sup> Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at [www.christiedigital.com](http://www.christiedigital.com)

